

The photo may show the standard model and not the configurated one

Catalogue
FOOD SERVICE
Chapter
DISTRIBUTION

Specific model
CCHF-10 230V 1N 50/60Hz

19044546 19/06/2024


DENOMINATION:

Hot trolley with humidity control CCHF-10 capacity 10 levels GN 2/1 with guide spacing of 70mm.

DESCRIPTION :

- All parts of the trolley have been carefully analysed and tested to offer maximum temperature performance in the interior, bearing in mind the following most important requirements: ease of use, minimum maintenance and facilitation of
cleaning tasks.
- Modern and intuitive electronic control panels.
- Double walled sides and door, insulated with high density polyurethane, giving great robustness and firmness.
- Recessed monoblock guides with wide radius, guaranteeing maximum hygiene.
- Efficient heat production system composed of heating element and fan.
- Recessed water reservoir with rounded corners. The heat is produced by a high-performance silicon heating element.
- 4-level humidity regulation system to adapt to the different products kept inside. The humidity system can also be fully switched off, reducing energy consumption.
- The 270° opening door offers users maximum freedom of movements and safety during daily use, increasing comfort and well-being during work operations.
- The inner door panel is completely smooth and free from any elements that might prevent thorough cleaning.
- No heat loss. Door seal fixed to the frame of the structure. Can be replaced easily without the need for tools.
- The whole perimeter is protected by a bumper, manufactured in resistant, nonmarking material.
- Pivoting wheels, 2 with brakes.
- Manufactured completely in AISI-304 stainless steel.
- Heat system designed to reach the operational temperature in a very short space of time.
- Electronic membrane keypad and digital display.
- Ergonomic latch with lock.
- Modern, elegant and very robust design.
- Storage of GN 2/1 trays.
- Shelves and Gastronorm pans are not included.

DIMENSIONS



X Width	790 mm	X Gross width	1085 mm
Y Depth	935 mm	Y Gross depth	940 mm
Z Height	1215 mm	Z Gross height	1315 mm
Net Weight	80,0 kg	Gross Weight	90,0 kg
Net volume	1,341 m3	Gross volume	1,341 m3

ELECTRICITY TECHNICAL SPECIFICATIONS

Electric power	2,000 kW
Voltage	230V
Phases	1N
Electric frequency	50/60Hz
Amperage (A)	9A

COLD TECHNICAL SPECIFICATIONS

Termperature	+30/+90

CONNECTIONS TECHNICAL SPECIFICATIONS

Single-phase 230V wiring	2X1,5 - 10 A

TECHNICAL FEATURES

Number of trays	10



Catalogue
FOOD SERVICE
Chapter
DISTRIBUTION

Specific model
CCHF-10 230V 1N 50/60Hz

19044546 19/06/2024



