CURVED BONVUE FOOD DISPLAYS

BONVUE

- 3 adjustable levels of wire shelving plus floor
- LED lighting over each level
- Self evaporating drainage
- Black trim
- Castors
- Triple glazed front with heated filaments to stop condensation
- Sliding glass rear doors
- Ambient 40ºC & 40% RH
- Digital temp. control & read-out
- Fan-forced thermal air-flow & humidity



Code	GEMS Star Rating	Dimensions (WxDxH mm)	Weight (kg)	Temperature Range °C	Ambient/ RH%	Voltage	Power (W/A)
Chilled Displays							
SL830	4	900x740x1350	260	+2 to +8	40/40	240	616/10
SL840	4	1200x740x1350	295	+2 to +8	40/40	240	785/10
SL850	4	1500x740x1350	345	+2 to +8	40/40	240	878/10
SL860	4	1800x740x1350	390	+2 to +8	40/40	240	1045/10
Heated Displays							
H-SL830	–	900x740x1350	200	+30 to +85	40/40	240	870/10
H-SL840	–	1200x740x1350	240	+30 to +85	40/40	240	975/10


Allow 100mm clearance for installation, all vents must be left clear. Heated cabinets are for hot food holding only, not designed to heat product.
Prices and specifications are subject to change without notice. Pictures are for illustrative purpose and final product may differ


CURVED BONVUE FOOD DISPLAYS

BONVUE

SL830/H-SL830









SL840/H-SL840









SL850







SL860



