



	<b>WATER CONNECTION 3/4" GAS</b>
	<b>DRAIN PIPE Ø 32mm</b>
	<b>ELECTRICAL SUPPLY</b>

TECHNICAL DATA	STANDARD			
<b>EXTERNAL DIMENSIONS</b>				
width	840 mm			
depth	885 mm			
height	1790 / 2050 mm			
WEIGHT	199 kg			
VOLTAGE	400V 3N 50Hz			
POWER EQUIRED	12500 W			
WATER HARDNESS	2-8 °F			
INLET WATER PRESSURE	200 - 400 kPa			
<b>CROCKERY DIMENSIONS</b>				
max. tray height	645 mm			
RACK DIMENSIONS	700 x 700 mm			
RACK EQUIPMENT	1 x spatula basket - 1 x tray support - 1 x s/steel basket			
WASHING CYCLES (min)	1(3)	2(6)	3(9)	4(12)
<b>WATER SUPPLY 55°C</b>				
rack/h <sup>(*)</sup> (1)	20	10	6	5
<b>WATER SUPPLY 10°C</b>				
rack/h <sup>(*)</sup> (1)	20	10	6	5
WATER CONSUMPTION / CYCLE	4.3 L			
BOILER CAPACITY	20 L			
BOILER HEATING ELEMENT	9000 W			
RINSING TEMPERATURE (SET)	85 °C			
TANK CAPACITY	78 L			
TANK HEATING ELEMENT	6000 W			
TANK TEMPERATURE (SET)	55 °C			
WASHING PUMP POWER	1750 W (810 L/min <sup>***</sup> ) x 2			
RINSING PUMP POWER	250 W (150 L/min <sup>***</sup> )			
DRAIN PUMP (optional)	190 W (120 L/min <sup>***</sup> )			
NOISE	69.9 dB(A)			

(\*) STANDARD THERMOSTOP

(\*\*\*) MAXIMUM FLOW RATE

<sup>1)</sup> In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash -cycle total timing might result longer than set.