

CG14-2TP DUAL LID CONTACT GRILL

Prince Castle's dual lid contact grill has two heated platens that consistently cook a variety of products from top and bottom. Each platen's temperature is independently regulated/maintained by solid state controller and four zone probe monitoring.

With two four-channel electronic, programmable timers, the Prince Castle contact grill incorporates an audible alarm to supervise and remind operators to check or remove products.

The CG14-2TP contact grill has a cool exterior base surface and upper platen guards provide added protection from the top heated surfaces during operation. Platen temperature set points are pre-programmed with built -in set point adjustment protection. Removing product build-up is simple with removable catch/drip tray.

Adjustable four position lid stops are also designed specifically for repetitive menu items and include closed position set point for daily cleaning.



CG14-2TP

STANDARD FEATURES:

- Solid state controls provide accurate temperature control
- Cooking surface is 355mm wide
- Cooking surface temperature range = 79°C to 302°C
- Durable stainless steel construction and heavy duty platens ensure long life and reliability
- Dual four channel electronic, programmable timers to track product grill times
- Adjustable four position lid stops provide consistent grilling of menu items and adjustment for cleaning
- "Slide in, Slide out" control board feature allows for menu changes through accessible USB port and quick change out during any required service replacement
- Easy to clean grease drawer accessible from front
- FSM exclusive 13 month parts and labour warranty



"Slide in, Slide out" control board feature



Adjustable lid stops for each upper platen





(FOOD SERVICE MACHINERY PTY. LTD.)



CG14-2TP DUAL LID CONTACT GRILL

SPECIFICATIONS





Designs and specifications are subject to change without notice.

DIMENSIONS:

Model Number	Width (cm)	Height (cm)	Depth (cm)	Shipping Weight (kg)	Shipping (cu.m.)
CG14-2TP (Closed)	41.90	28.40	56.60	35.00	.175
CG14-2TP (Open)	41.90	79.90	56.60	35.00	.175

ELECTRICAL:

Model Number	Volts	Hz	Watts
CG14-2TP	240	50	2600

Units supplied with 15A plug