


Air Curtain Display

TOAM-48-HC~NSL01

 Upright Open Multideck Refrigerator



Dimensions		Build		Technical	
External Width (mm)	1220	Exterior Construction	Aluminium or Black powder coated Steel	Temperature Holding	0.5 : 3.3°C
External Depth (mm)	757	Interior Construction	Clear or White coated aluminium, stainless steel base	Refrigerant	R290
External Height (mm)	1994	Air Intake Position	Front	Voltage / Frequency / Phase	220-240V/50Hz/1
Net Volume (Litres)	547	Ventilation Position	Rear	Amps	10
Gross Volume (Litres)	963	Clearance Required	102 mm rear, 305 mm above	60Hz model Amps	11
Display Area (m ²)	1.09	Cord Length (Meters)	3.04	Wattage	2300
Supplied Shelves	4	Internal Lighting	LED	60Hz model Wattage	2530
Shelf Size (L x D mm)	1120 x 425			Defrost Type	Auto
Internal Net Height (mm)	1150				
Unpackaged Weight (kg)	234				
Packaged Weight (kg)	245				
Packaged Dimensions (W x D x H mm)	1321 x 889 x 2134				
Supplied Supports	Leg Levellers (Castors supplied separate)				



Specifications subject to change without notice.
Technical data above related to energy use based on testing of 50Hz or Dual Frequency models
Chart dimensions rounded up to the next whole millimeter (inches rounded up to the 1/8")


UK & Ireland [0800 783 2049](tel:08007832049)
EMEA [+41 61 563 07 05](tel:+41615630705)
Australia [+61 2 9619 9999](tel:+61296199999)

TFIUK@truemfg.com
TrueCHCustomerService@truemfg.com
TrueRefAus@truemfg.com



TOAM-48-HC~NSL01

 Upright Open Multideck Refrigerator



Specifications subject to change without notice.
Technical data above related to energy use based on testing of 50Hz or Dual Frequency models
Chart dimensions rounded up to the next whole millimeter (inches rounded up to the 1/8")

UK & Ireland [0800 783 2049](tel:08007832049)
EMEA [+41 61 563 07 05](tel:+41615630705)
Australia [+61 2 9619 9999](tel:+61296199999)

TFIUK@truemfg.com
TrueCHCustomerService@truemfg.com
TrueRefAus@truemfg.com

