

OVENS

Code BCKGS40 **Model** BCKGS40



GAS COMBI OVEN DIRECT STEAM GENERATION - 40 GN1/1 - 20 GN2/1 WITH ROLL-IN TROLLEY

General characteristics



HIGH TECH - S CONTROL

Technical/functional characteristics

Manual controls with electronic control, 99 programs and 4 cycles in automatic sequence can be programmed. Dedicated button for managing 4 cycles with display LED. Over 90 recipes tested and stored recipes (S version with probe). For those without a probe, only dedicated recipes are set. Burner setting with direct access from control panel, display alphanumeric, button for direct access to the programs and recipes. Combiclima with Fast-Dry automatic vent, self-diagnosis, automatic reverse (distribution of the air in the chamber with automatic reversing of the fan direction), humidifier and cavity lights. OPTIONAL: Multipoint probe, hand shower, automatic washing system WCS (Washing Combi System) with 4 washing levels (including rinsing)

OPERATING MODES

- Convection with Combiclima 30°C - 300°C
- Steam 30°C - 130°C (low temperature, atmospheric, forced)
- Combined steam/convection with Combiclima 30°C - 300°C
- Reheating with Combiclima 120°C - 140°C
- Automatic sequence cooking
- Temperature hold with Combiclima function

FUNCTIONS

- 99 programs, 4 cycles in automatic sequence
- Over 90 tested and stored recipes (S version with probe). For those without a probe, only dedicated recipes are set
- Temperature hold function
- Manual washing program
- Boiler descaling program
- Motorized manual vent
- Combiclima with fast-dry
- USB Port
- Two speed fan

Technical Data

Dimensions		Cold soft water connection (Ø)	
Width (mm)	1293	Drain (Ø)	50 mm
Depth (mm)	899	Gas power (KW)	54

BARON CUCINE PROFESSIONALI - ALI GROUP S.P.A.

32100 - Belluno - Italy - via del Boscon, 424

Tel. 0437 8554 - Fax 0437 855444

E-mail: info@baronprofessional.com

Website: www.baronprofessional.com

OVENS

Code BCKGS40 **Model** BCKGS40



GAS COMBI OVEN DIRECT STEAM GENERATION - 40 GN1/1 - 20 GN2/1 WITH ROLL-IN TROLLEY

Height (mm)	1810
Gas connection (Ø)	-
Electric connection (V/~ /HZ)	230
Cold water connection (Ø)	3/4"
Hot water connection (Ø)	-

Electric power (KW)	1.8
Plate dimensions (mm)	-
Tank capacity (Lt)	-
TANK DIMENSIONS	-
Internal ovens dimension(mm)	20 GN2/1 - 40 GN

Code	Description
KSA001	NEEDLE-CORE TEMPERATURE SENSOR FOR VACUUM COOKING - Ø 1 MM
RP004	CASTOR KIT 2 WITH BRAKE - FLANGED CASTORS
HKS202	TROLLEY WITH DRIP TRAY - EQUIPPED WITH 1
KSC004	NEEDLE-CORE TEMPERATURE SENSOR
CP202	RACK THERMAL COVER - 40 GN1/1
KFX202	FAT FILTER
LD25	SHOWER FOR OVEN CAVITY WITH STAINLESS STEEL HOSE, FITTING AND CONNECTIONS
dL010	ALKALINE CLEANSER (TANK 10 LT)
KLT202	AUTOMATIC WASHING SYSTEM FOR OVENS 40 GN1/1
PL002	NEBULIZE FOR CLEANSER
dS010	ALKALINE DESCALER FOR BOILER (TANK 10 LT)
KP004	SET OF FEET
PL005	NEBULIZE FOR CLEANSER - 5 LT
HKP202	TROLLEY FOR BANQUETING WITH DRIP TRAY