



Project: Item:





Standard Features:


- AISI 304 Grade Stainless Steel Construction
- Energy efficient heat exchange system
- Insulated heat exchange chamber
- Three Jet Burner fitted with Flame Failure & Auto Ignition
- Overheat tank protector device fitted
- Tank auto refill & Pressure release valve installed
- Three Stop rotary door lock system
- Drain tank valve
- 12-month Warranty
- XSENTIAL Water Filtration Included.
- QF-9 Filtration System: QLD, NSW, ACT, VIC, TAS
- XP-195 Filtration System: NT, SA, WA

Options:

Natural or LP Gas







MODEL	LENGTH	DEPTH	HEIGHT	WEIGHT	GAS CONSUMPTION (Mj/h)	
	(mm)	(mm)	(mm)	(kg)	NG	LPG
DSK-3	900	885 Unit 940 w/Rail	1950	296	150	150

Connections:

	GAS (GI) WATER		TANK DRAIN	SUPPLY PRESSURE (kPa)		
(BSP) (WI)	(BSP)	(BSP)	NG	LPG	
³⁄₄" (N	Non-Return Isolating Valve 15 mm Female Flared	2" (M)	2" (F)	1.0	2.6	

- Regulator is included in the unit
- Must be installed by an authorised installer
- Warranty Voided if water filtration device is not installed

Due to ongoing Product Development, Product Improvement and Research, B+S Commercial Kitchens reserves the right to alter specification without notice.



