

## 3 Phase Hood Type Dish & Glasswasher for Straight or Corner Applications



### Product Advantages:

- **Easy-to-use** electronic controls with 2 cycles - 75 & 150 seconds
- Electronic temperature gauges
- Suitable for all dish & glass washing applications. **Useable chamber height of 440mm.** Able to wash 1/1 GN pans when using optional open ended tray racks
- **Low 2.9 litres per cycle rinse volume** dish / glasswasher
- **Fully enclosed 4 sided hood** design - avoiding loss of energy / steam
- Optimum hygienic - deep drawn tank with covered corners (no welds) and **SELF-CLEANING CYCLE**
- Polypropylene wash and stainless steel rinse arm with **patented WIDE ANGLE FAN** nozzle to maximize wash & rinse performance
- Wash pump inlet strainer to ensure machine reliability
- Includes fill hose, power lead, pump-out drain for quick & easy installation & chemical dispensers
- Includes 1 x plate rack & 1 x cutlery holder
- Back flow prevention device as standard to meet Watermark Approval & ATS 5200.101

### Technical Data

drain connection	Pump-out drain standard - 20mm inner / 25mm outer diam.
fresh water connection: pressure hose 1000mm	Connection size: 3/4" BSP
flow pressure	50-1000kPa
incoming water temperature	55-65°C
power cord	15amp single phase plug & lead
hose for detergent hose for rinse aid	Optional accessories
wash tank temperature	55-65°C
rinse water temperature (booster tank)	Minimum 82°C
low temp cut-out (thermostop) activated	Yes
cycle times	75 sec. 150 sec.
water consumption	2.9litres
tank capacity	21 litres
tank heating	2.5kW
power supply	240/50/3 NE
booster loading	2.6kW
total loading	3.2kW
pump capacity	0.4kW
loading height	440mm
bench to bench - internal dimension	628mm

Water hardness should not exceed 3°dH, if higher we recommend using a water softener.

If mineral content is high a demineraliser may be advisable.

