

Edlund Crown Punch Can Openers

Edlund Crown Punch models offer remarkable productivity and reliable operation. Choose from the manual 700SS or the higher capacity pneumatic 610 & 625 models that best suit your volume requirements.



Model 700SS



Model 610



Model 625

The manual 700SS unit opens the can with a single stroke, and comes complete with knife and guard ring locator for one standard size #10 round can. All stainless steel manufacture including the mechanism. Suits 6-10 cans/minute requirement (up to 200 cans per day).

(Note compressor not included)

The pneumatically powered Model 610 offers even more capacity with minimum labour or fatigue. When you need productivity and reliable performance, Edlund Crown punch units deliver. Suitable for production requirements up to 400 cans per day.

(Note compressor not included)

The pneumatically powered heavy throughput Model 625 offers even more capacity with minimum labour or fatigue.

Ideal for high volume food producers/processors, Edlund pneumatic Crown punch units deliver optimum performance and reliability.

Suitable for production requirements of up to 2000 cans per day.

(Note compressor not included)

FSM (FOOD SERVICE MACHINERY PTY. LTD.)
HEAD OFFICE: UNIT E6, 63-85 TURNER STREET,
PORT MELBOURNE, VIC. 3207 AUSTRALIA
T: +61 3 8645 2555 F: +61 3 8645 2565
E: sales@fsm-pl.com.au W: www.fsm-pl.com.au

SYDNEY OFFICE:
UNIT 15, 7-9 PROGRESS CIRCUIT,
PRESTONS, NSW 2170 AUSTRALIA
T: +61 2 9608 8620 F: +61 2 9607 9370
E: sales@fsm-pl.com.au W: www.fsm-pl.com.au

QUEENSLAND:
T: 0400 099 992
E: sales@fsm-pl.com.au
W: www.fsm-pl.com.au



Model 700SS



Model 610



Model 625

MODEL	AIR REQUIREMENT	CAPACITY	HEIGHT(cm)	CUBE m3	CASE WEIGHT KGS
700SS	Manual Handle	Up to 200 cans/day	50.8 to 77.5H	0.08	18.6
610	85-120PSI 1-2CFM	Up to 400 cans/day.	53.3	0.5	36
625	85-120PSI 1.5-2CFM	300-2000 cans/day.		0.36	64

Can Heights: 5.1cm - 26.6cm

Max. Can Diameters: 16.6cm

Compressor not included in pneumatic models

STANDARD TOOLING:

Can Size	(inches)	(mm)
603 (#10)	6 3/16	157 mm
600	6	152.4 mm
502	5 1/8	130 mm
404	4 1/4	108 mm
401	4 1/16	103.2 mm
400	4	101.6 mm
307 (SOUP)	3 7/16	87.3 mm
303	3 3/16	81 mm
300	3	76.2 mm
214	2 7/8	73 mm
211	2 11/16	68.3 mm
202	2 1/8	54 mm

Note: Custom tooling available. Please call