

GC100 IP STD

20 x 1/1GN roll in blast chiller/freezer

functions

Blast chilling cycles +3°C HARD/SOFT

Blast freezing cycles -18°C HARD/SOFT

Max. chilling capacity (+3°C) / kg **160**

Max. freezing capacity (-18°C) / kg **110**

Climatic class **4**

technical data

Width (mm) **1300**

Depth (mm) **1330**

Height (mm) **2100**

Weight (kg) **410**

N° trays 1/1GN (535x325) or 600x400 **20**

N° trays trolleys 1/1GN **1**

Electric connection (V/~ /Hz) **420/3/50
+ N**

Electric power (W) **755**

Max. absorbed current (A) **5.47**

Compressor (HP) **10**

Refrigerant type (gas) **R452A**

Internal width (mm) **740**

Internal depth (mm) **940**

Internal height (mm) **1700**

Gross weight (kg) **570**



main features

- Full Touch 7-inch Display
- Finely “Scotch Brite” brushed exterior
- 80 mm insulation thickness in CFC and HCFC-free PU, density 42 kg/m³
- 2mm stainless steel floor
- Large storage capacity cell featuring rounded corners for easy cleaning
- Ergonomic handles
- Front electric panel that can be fully inspected
- Drain
- Air distribution with new evaporator deflector
- OPTIONAL electronic expansion valve
- PLUS versions ventilation regulation by inverter
- Connectivity 4.0
- Load capacity pursuant to EN17032
- OPTIONAL weather sealed and soundproofed condensing units

GC100 1P STD

20 x 1/1GN roll in blast chiller/freezer