



	<b>WATER CONNECTION 3/4" GAS</b>
	<b>DRAINING PIPE Ø 24mm</b>
	<b>ELECTRICAL SUPPLY</b>

TECHNICAL DATA		STANDARD			
<b>EXTERNAL DIMENSIONS</b>					
width	450 mm				
depth	535 mm				
height	700 mm				
WEIGHT	37 kg				
VOLTAGE	240V 50Hz				
POWER REQUIRED	3200 W				
WATER HARDNESS	2-8 °F				
INLET WATER PRESSURE	200 - 400 kPa				
<b>CROCKERY DIMENSIONS</b>					
plates diameter	295 mm				
dishes max. height	305 mm				
RACK DIMENSIONS	400 x 400 mm				
RACK EQUIPMENT	2 x glass basket - 1 x saucer holder - 1 x cutlery container				
WASHING CYCLES (secs)	1(60)	2(90)	3(120)	4(180)	
<b>WATER SUPPLY 55°C</b>					
rack/h(*) <sup>(1)</sup>	60	40	30	20	
<b>WATER SUPPLY 10°C</b>					
rack/h(*) <sup>(1)</sup>	16	16	16	16	
WATER CONSUMPTION / CYCLE (water pressure 200kPa)	1.8 L				
BOILER CAPACITY	3.4 L				
BOILER HEATING ELEMENT	2800 W				
RINSING TEMPERATURE (SET)	85 °C				
TANK CAPACITY	14.5 L				
TANK HEATING ELEMENT	1250 W				
TANK TEMPERATURE (SET)	55 °C				
PUMP POWER	400 W (185 L/min <sup>***</sup> )				
DRAIN PUMP (optional)	25 W h max draining 0.8 m (40 L/min <sup>***</sup> )				
NOISE	60.6[CF] 61.2[LS] (db(A)±0.7)				

(\*) STANDARD THERMOSTOP

(\*\*\*) MAXIMUM FLOW RATE

<sup>1)</sup> In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash -cycle total timing might result longer than set.