



Ergonomics in all stages

The leaning design means that the feed cylinder is always positioned at the right angle – the machine is easy to top up. Using HALLDE Power Link you get a leverage effect from the pusher plate. The result is that you need almost 50 percent less manual power. For a better working posture, the pusher plate has a looped designed handle, HALLDE ErgoLoop, which means you can work with both your left and right hands. We recommend our vertically adjustable machine table to ensure you always work at the right height when using the machine.



Safe and quick top ups

Thanks to the automatic start and stop function the machine stops as soon as the pusher plate is swung aside. When it is swung back the machine restarts and you can continue working. The RG-250 also has a full moon cylinder that can hold larger quantities and whole products. Features like these are a clear advantage, particularly when larger volumes are involved.



do not need to buy new cutting tools. Always perfect cutting results

direct-driven cutting tool. No belts or

intermediate connections. The power

from the motor goes via a maintenance

free gear drive. This makes the RG-250

Our wide range of cutting tools means

to make you even more efficient in the kitchen. The RG-250 slices, dices, shreds,

the RG-250 can handle every conceivable

grates, cuts juliennes and crimping slices everything from firm to soft products.

The knife blades and grating plates are

replaceable. As a result you

task. You choose the cutting tool you need

an exceptionally reliable machine -

irrespective of the products you are

Cutting tools with

complete register


preparing.

The rotation speed of the cutting tools is optimised for cutting fine and even slices as efficiently as possible. The knife blades are purposely sharpened to avoid inertia or the edge breaking off.



If the feed cylinder is removed the power is cut. Thanks to this double security there is no risk of the machine starting with an unprotected cutting tool.

Developed for the best hygiene





Easy cleaning

For quick cleaning are all loose parts simple to remove for easy rinsing of the machine. The pusher plate and feed cylinder are removable and can be cleaned under running water.

Only the best material

Machine base, feed cylinder and pusher plate are all made of robust metal. Only top quality stainless steel is used to manufacture the cutting tool knife blades.

Lightweight and easy to move



RG-250 Accessories

The relatively small size of the machine gives several advantages. It doesn't take up a lot of space in the kitchen. And it is easy to move, something which is helped by the generously sized handle on the back.

Highest possible reliability

The powerful motor has a high starting and running torque and powers the



Machine Table



Container Trolley



Wall Rack



Brush

High quality cutting tools for best results

All cutting tools are dishwasher safe.



Slicer

(stainless steel) 0.5, 1, 1.5, 2, 3, 4, 5, 6, 7, 8, 9, 10 mm. Are designed to slice firm and soft vegetables, fruits, mushrooms etc.

Dices when combined with a suitable Dicing Grid.
Cut French fries in combination with French Fry Grid.





Standard Slicer

20 mm.

Are designed to slice firm products, such as root vegetables etc.

Dices when combined with a suitable Dicing Grid.





Fine Cut Slicer

15 mm.

Are designed to slice firm and soft vegetables, fruits, mushrooms

Dices when combined with a suitable Dicing Grid.





Soft Slicer

8, 10, 12, 15 mm.

Are designed to slice soft vegetables, fruits, mushrooms etc. Preferably used when dicing soft products, in combination with a suitable Dicing Grid.





Crimping Slicer

(stainless steel) 2, 3, 4, 5, 6 mm. Cut decorative rippled slices of beetroot, cucumber, carrots, etc.





Julienne Cutter

(stainless steel) 2x2, 2x6, 3x3, 4x4, 6x6, 8x8, 10x10 mm. $\mbox{\it Cut}$ julienne of firm products for soups, salads, stews, decorations etc.

Suitable to cut slightly curved French fries.





Grater/Shredder

(stainless steel) 1.5, 2, 3, 4.5, 6, 8, 10 mm. Grates carrots and cabbage for raw salads. Grates nuts, almonds and dry bread.

Grater 6 or 8 mm is commonly used for grating cheese for pizza and when shredding cabbage.





Fine Grater Extra Fine Grater

Hard Cheese Grater


(stainless steel)

Suitable to grate products very fine such as raw potatoes for potato pancakes, hard/dry cheese to a powder, such as Parmesan for pasta.

Grates dry bread into crumble and horse radish into sauce etc.

Hard Cheese Grater ideal for grating hard cheese such as parmesan.





Dicing Grid

6x6, 8x8, 10x10, 12x12, 15x15, 20x20, 25x25 mm.

Are designed to cut dices in combination with a suitable type of slicer. Dice both hard and soft vegetables, fruits etc.





French Fry Grid

10x10 mm

Cuts straight French fries in combination with Slicer 10 mm.



















Made in Sweden since 1941

RG-250 Vegetable Preparation Machine

- Large full moon feed cylinder that can take most items whole.
- Direct driven cutting tools from a strong heavy duty motor with planetary gear transmission.
- "HALLDE PowerLink" provide a leverage effect on the pusher plate which reduces the manual pressure needed to about half.
- "HALLDE ErgoLoop" enables the user to use both hands when operating the machine.
- Leaning design and support wall for easy piling of tomatoes, onions etc. for oriented slicing.

Machine

- Motor: 0.55 kW. One-speed. 100 V, single phase, 50-60 Hz. 110-120 V, single phase, 60 Hz. 220 V, single phase, 50 Hz. 230-240 V, single phase, 50 Hz. 230 V, three phase, 50 Hz. 400 V, three phase, 50 Hz. 440 V, three phase, 60 Hz.
- Transmission: Planetary gearing.
- Safety system: Two safety switches.
- · Degree of protection machine: IP44.
- Degree of protection push buttons: IP65.
- Power supply socket: Earthed, single phase. 10 A alternatively earthed, three phase, 16 A.
- Fuse: 10 A, delayed action fuse.
- Sound level LpA (EN31201): 72 dBA.
- Magnetic field: Less than 0.5 microtesla.

Materials

- Machine housing: Anodized or polished aluminium alloy.
- Cutting tool discs: Stainless steel/ Aluminium/ Fiberglass reinforced polyamide.
- Cutting tool knife blades: Stainless knife steel.
- Machine table: Stainless steel.
- Container: Polycarbonate.

Feeder

- Feed cylinder, volume 4 litre, height 180 mm, diameter 170 mm. One fixed internal support wall 55 mm wide.
- Feed tube with internal diameter 56 mm.
- · Pusher plate with "HALLDE ErgoLoop" handle and "HALLDE PowerLink" lever system.

Cutting tools

- Diameter: 185 mm.
- Speed: 350 rpm (50 Hz), 420 rpm (60 Hz).

Type of preparation

- Slices, dices, grates, shreds, cuts julienne and crimping slices.
- · Processes vegetables, fruit, dry bread, cheese, nuts, mushrooms, etc.

Users

· Restaurants, shop kitchens, diet kitchens, retirement homes, hospitals, schools, fast food outlets, catering, day care centers, pizzerias, ships, central kitchens, institution kitchens, etc.

Net weights

- · Machine: 21 kg.
- · Cutting plates: 0.5 kg.

Standards

- NSF/ANSI Standard 8.
- Other directives: Visit hallde.com. Select product and "Certification".

