



	WATER CONNECTION 3/4" GAS
	DRAIN PIPE Ø 32mm
	ELECTRICAL SUPPLY

TECHNICAL DATA	STANDARD				
EXTERNAL DIMENSIONS					
width	690 mm				
depth	800 mm				
height	1890 / 2275 mm				
WEIGHT	155 kg				
VOLTAGE	400V 3N 50Hz				
POWER EQUIRED	8180 W				
WATER HARDNESS	2-8 °F				
INLET WATER PRESSURE	200 - 400 kPa				
CROCKERY DIMENSIONS					
max. tray height	805 mm				
RACK DIMENSIONS	550 x 665 mm				
RACK EQUIPMENT	1 x spatula basket - 1 x s/steel basket - 1 x tray support - 1 x grid				
WASHING CYCLES (secs)	1(120)	2(240)	2(360)	3(480)	4(600)
WATER SUPPLY 55°C					
rack/h ^(*) (1)	30	15	10	7.5	6
WATER SUPPLY 10°C					
rack/h ^(*) (1)	16	15	10	7.5	6
WATER CONSUMPTION / CYCLE	4.2 L				
BOILER CAPACITY	15 L				
BOILER HEATING ELEMENT	6000 W				
RINSING TEMPERATURE (SET)	85 °C				
TANK CAPACITY	50 L				
TANK HEATING ELEMENT	3000 W				
TANK TEMPERATURE (SET)	60 °C				
WASHING PUMP POWER	2180 W (810 L/min ^{***})				
RINSING PUMP POWER	250 W (150 L/min ^{***})				
DRAIN PUMP (optional)	190 W (120 L/min ^{***})				
NOISE	63.8 dB(A)				

(*) STANDARD THERMOSTOP (CANNOT BE DISABLED)

(^{***}) MAXIMUM FLOW RATE

¹⁾ In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash -cycle total timing might result longer than set.