



## PRODUCT ADVANTAGES

- Compact glasswasher: installation height of only 705 mm.
- Electronic control with digital temperature indication and 3 programmes for easy operation.
- GENIUS-X fine filter system: ensures the best wash result and saves energy and detergent costs.
- CLIP-IN wash and rinse arms: wash and rinse arms can be removed without any tools.
- Thermostop function: automatic cycle time control to achieve hygienic rinsing temperatures.
- Double-walled housing: the machine is double-walled, soundproof and heat-insulated.
- Smooth counterbalanced door: soft, silent opening and closing. The dishwasher doors have gas-filled shock absorbers to protect your tableware and prevent wear of the door suspension.
- Optional refill signal: monitors contents of external chemical containers at any time. The control indicates well in advance when detergent and rinse aid need refilling.
- Thermolabel 71 °C: default temperatures setting acc. European DIN can be switched by operator to a higher thermolabile setting.
- Watermark approved
- Made in Germany

## TECHNICAL DATA

Cycle times*	60 / 90 / 120 sec. and self-cleaning programme
Water consumption	2.0 l/rack
Tank capacity	10.6 l
Tank heating	1.7 kW
Power supply	240 / 50 / 1 (415 / 50 / 3N)
Booster loading	
Standard	2.1 kW
Alternative	6.2 kW
Total loading	
Standard	2.7 kW   15 A
Alternative	6.8 kW   3 x 15 A
Wash pump	0.5 kW
Rack size	500 x 500 mm
Loading height	305 mm
Noise level	59 dB (A)
Weight (gross/net)	70 / 60 kg

\* The machine is equipped with an automatic programme time extension which ensures hygienic rinse temperatures, even on a cold-water supply or 240 V connection.

To avoid spots and streaks on the wash ware, we recommend the usage of a demineralisation cartridge (HYDROLINE STAR / STAR EXTRA) or a reverse osmosis system HYDROLINE PURE (please refer to HOBART Export price list 2022, chapter 1.6).

## CONNECTIONS

(1) Drain hose	2,000 mm ID20 / AD25
(2) Supply hose	2,000 mm   R 3/4"
Required flow rate	5 l/min
Flow pressure	0,5 - 10 bar
Max. supply temperature	60 °C
(3) Connection cable	2,000 mm
Supply hose for	
(4) Detergent	2,500 mm
(5) Rinse aid	2,500 mm

## DRAWING

