

VERTICAL DISPLAY & STORAGE

Fan Forced Glass Door Chillers

BROMIC
REFRIGERATION

- Internal bright light promotes impulse sales
- Illuminated advertising display lightbox
- Corrosion resistant outer body
- Door mechanism holds door open making it easier to place and take out products
- Quick chill blower system will ensure homogenous coolness in the storage space
- Environmentally friendly refrigerant (CFC & HCFC Free) R134a
- Automatic defrost system, saves energy consumption and provide shortest possible defrost cycle



Glass Door Chiller
W/ Lightbox 444L LED
GD0500LF



Glass Door Chiller
W/ Lightbox 976L LED
GD1000LF






Glass Door Chiller
W/ Lightbox 1507L LED
GD1500LF

GD0500LF

GD1000LF

GD1500LF

	GD0500LF	GD1000LF	GD1500LF
Bromic Part Number	3736225	3736226	3736227
Capacity - Gross (litres)	444L	976L	1507L
External Dimensions (mm)	635w x 760d x 2060h	1260w x 760d x 2060h	1880w x 760d x 2060h
<small>Depth dimensions exclude lightbox and handle protrusions</small>			
Internal Dimensions (mm)	520w x 595d x 1435h	1143w x 595d x 1435h	1755w x 595d x 1435h
Temperature range (°C)	+2 to +8°C	+2 to +8°C	+2 to +8°C
Max. ambient temp °C/RH%	32°C/60%	32°C/60%	32°C/60%
Refrigeration Power (Watts)	740W	1000W	1132W
Current (Amps)	4.5A	5.6A	7.0A
Plug Supplied	Yes, 10amp	Yes, 10amp	Yes, 10amp
Light Display Box	Yes	Yes	Yes
Interior light	LED	LED	LED
No. Of Doors	1 Non Reversible	2	3
Door Material	Double Glazed Thermo Glass	Double Glazed Thermo Glass	Double Glazed Thermo Glass
Door Lock	No	No	No
Temperature controller	Digital	Digital	Digital
Number of shelves	5	5 + 5	5 + 5 + 5
Gross weight (kg)	95Kg	157Kg	209Kg
Refrigerant	R134a	R134a	R134a
Colour	White With S/Steel Trim	White With S/Steel Trim	White With S/Steel Trim
Power Usage (at 30 °C/60%RH)	8.37KWh/24hr	10.55KWh/24hr	11.96KWh/24hr



Danfoss



WARRANTY 1 YR PARTS
1 YR LABOUR