

BAR CHILLERS & FREEZERS

Glass Door Chillers

BROMIC
REFRIGERATION



**Glass Door Underbench
Chiller 282L LED**
UBC1360GD



**Glass Door Underbench
Chiller 417L LED**
UBC1795GD






**Glass Door Underbench
Chiller 553L LED**
UBC2230GD

The Bromic range of high specification underbar storage chillers are ideally suited for professional use in restaurants, bars, hotels, clubs, cafes and all high volume food preparation areas. Suitable for storage of meat, dairy products, vegetables and drinks.

- Available in three sizes, 2 door, 3 door and 4 door
- 50mm insulation for increased energy efficiency
- Forced air cooling ensures consistent internal temperatures
- Advanced Dixell controller provides:
 - ease of set point control
 - temperature display
- Alarm warning if condenser becomes blocked
- Energy efficiency control of compressor run time and defrost
- Essential cleaning made easy with removable shelf supports, curved internal corners and removable door seals
- Adjustable stainless steel gastronorm shelving with anti-tilt protection
- Self-closing doors
- Gastronorm 1 x 1 trays (530mm x 325mm)
- Lockable front castors
- Legs available
- Side mounted condenser has easy access door and removable, washable dust filter
- Internal LED lighting

GLASS DOOR	UBC1360GD	UBC1795GD	UBC2230GD
------------	-----------	-----------	-----------

Bromic Part Number	3735213	3735211	3735212
Capacity - Net (litres)	282L	417L	553L
External Dimensions (mm)	1360w x 700d x 860h	1795w x 700d x 860h	2230w x 700d x 860h
<small>Depth dimensions exclude lightbox and handle protrusions</small>			
Internal Dimensions (mm)	902w x 530d x 589h	1337w x 530d x 589h	1772w x 530d x 589h
Temperature range (°C)	+2 to +8°C	+2 to +8°C	+2 to +8°C
Max. ambient temp (°C/RH%)	32°C / 65%	32°C / 65%	32°C / 65%
Temperature control	Digital	Digital	Digital
Number of doors	2 hinged	3 hinged	4 hinged
External Material	Stainless Steel	Stainless Steel	Stainless Steel
Internal Material	Stainless Steel	Stainless Steel	Stainless Steel
Number of shelves	2 + 2 + Base	2 + 2 + 2 + Base	2 + 2 + 2 + 2 + Base
Power Consumption (Watts)	300W	320W	340W
Current (Amps)	2.2A	2.5A	2.8Amps
Plug Supplied	Yes, 10amp	Yes, 10amp	Yes, 10amp
Gross weight (kg)	113kg	151kg	173kg
Refrigerant	R134a	R134a	R134a
Insulation Gas	CFC free	CFC free	CFC free
Colour	Stainless Steel	Stainless Steel	Stainless Steel
Power Usage (at 30°C/60%RH)	2KWh/24hr	2.4KWh/24hr	2.8KWh/24hr



WARRANTY 1 YR PARTS
YR LABOUR