

These Ice Cream displays offer an attractive solution for display of ice creams. The units can be decal (charges apply POA)

- Curved display canopy for safety, hygiene and visual effect
- Easy clean condensor design for better protection-less condensation, less humidity - even in tropical climates
- Digital Temperature display
- Castors for easy positioning
- Corrosion resistant construction and equipped with defrost water drain



**Slim Angle Top Flat Glass Gelato Display - 7 Tubs**  
GD0007S/Slim



**Angle Top Flat Glass Gelato Display - 7 Baskets**  
GD0007S



**Angle Top Flat Glass Gelato Display - 7 Tubs**  
FENICE7



Sliding lid



Interior casting



Curved glass cover



5 litre storage tubs

	GD0007S/Slim	GD0007S	FENICE7
<b>Bromic Part Number</b>	3735311	3735262	3736205
<b>No. Of Baskets</b>	7 baskets	7 baskets	7 tubs
<b>External Dimensions (mm)</b>	1327w x 516d x 1229h	1298w x 615d x 1296h	1314w X 702d X 1165h
<small>Depth dimensions exclude lightbox and handle protrusions</small>			
<b>Internal Dimensions (mm)</b>	1210w x 395d x 705/630h	1180w x 495d x 708/610h	1190w x 505d x 755h
<b>Temperature range (°C )</b>	-12 to -22°C	-12 to -22°C	-12 to -22°C
<b>Max. ambient temp (°C/RH%)</b>	35°C / 70%	35°C / 70%	35°C / 70%
<b>Storage</b>	-	-	Rear Storage With Separate Temp Control
<b>Type Of Control</b>	Analogue	Analogue	Analogue
<b>Temperature display</b>	Digital	Digital	Analogue
<b>Front Glass</b>	Curved Tempered	Curved Tempered	Curved Tempered
<b>Product and Internal Lighting</b>	N/A	N/A	Fluoro
<b>Defrosting</b>	Manual	Manual	Automatic
<b>Airflow</b>	Static	Static	Static
<b>Power Consumption (Watts)</b>	300W	300W	1100W
<b>Current (Amps)</b>	2.3A	2.3A	6.7A
<b>Plug supplied</b>	Yes, 10amp	Yes, 10amp	Yes, 10amp
<b>Gross weight (kg)</b>	94kg	81kg	148kg
<b>Refrigerant</b>	R404a	R404a	R404a
<b>Colour</b>	White	White	White
<b>Power Usage (at 30°C/60%RH)</b>	4.9kWh/24hr	4.9kWh/24hr	15.1kWh/24hr

**WARRANTY 1** YR PARTS  
YR LABOUR