

## RI BT

1170L one door roll in refrigerated cabinet -20 / -15°C

### functions

Temperature range	<b>-20 / -15°C</b>
Climatic class	<b>5</b>

### technical data

Width (mm)	<b>880</b>
Depth (mm)	<b>1070</b>
Height (mm)	<b>2250</b>
Weight (kg)	<b>200</b>
Opening door depth 90° (mm)	<b>1850</b>
Capacity (L)	<b>1170</b>
N° trolleys 1/1GN (535x325) or 600x400	<b>2</b>
N° trolleys 2/1GN (535x650) or 600x800	<b>1</b>
Electric connection (V/~/Hz)	<b>230/1/50</b>
Electric power (W)	<b>955</b>
Max. absorbed current (A)	<b>5.4</b>
Cooling power (W)	<b>848</b>
Compressor (HP)	<b>1 1/4</b>
Internal width (mm)	<b>700</b>
Internal depth (mm)	<b>900</b>
Internal height (mm)	<b>1860</b>
Refrigerant type (gas)	<b>R452A</b>



### main features

- Panel construction (monocoque Mod.ROLL-INDX 1 TN COMPACT / ROLL-INDX 1 BT COMPACT).
- Capacity of the wheeled containers: GN 2/1 or EN 400x600 mm or 600x800 mm.
- Finely SCOTCH-BRITE sated exterior.
- PU, CFC and HCFC free insulation, thickness 80 mm (60 mm Mod. ROLL-INDX 1 TN COMPACT / ROLL-INDX 1 BT COMPACT), density 42 kgm<sup>3</sup> (back insulation 60mm).
- Automatic defrost and condensate evaporation device without the need for any electricity.
- Large capacity cell makes it possible to insert trolleys up to overall dimensions: 700x900x1860 mm.
- Ergonomic full height handles and magnetic seals on 4 sides.
- Standard lock with key.
- Self-closing doors with 100° opening lock.
- AISI 304 18/10 steel insulated floor for the LT version.
- Bumper on back and door interior in plastic material.
- Refrigerated versions (built-in condensing unit), versions without condensing unit with or without remote unit supplied by us.
- Versions with glass door.

