

RI TN COMPACT

800L one door roll in refrigerated cabinet +2 / +8°C

functions

Temperature range	+2 / +8°C
Climatic class	5

technical data

Width (mm)	760
Depth (mm)	850
Height (mm)	2090
Weight (kg)	150
Opening door depth 90° (mm)	1550
Capacity (L)	800
N° trolleys 1/1GN (535x325) or 600x400	1
N° trolleys 2/1GN (535x650) or 600x800	1
Electric connection (V/~ /Hz)	230/1/50
Electric power (W)	682
Max. absorbed current (A)	4.0
Cooling power (W)	506
Compressor (HP)	1/3
Internal width (mm)	630
Internal depth (mm)	740
Internal height (mm)	1730
Refrigerant type (gas)	R134A



main features

- Panel construction (monocoque Mod.ROLL-INDX 1 TN COMPACT / ROLL-INDX 1 BT COMPACT).
- Capacity of the wheeled containers: GN 2/1 or EN 400x600 mm or 600x800 mm.
- Finely SCOTCH-BRITE sated exterior.
- PU, CFC and HCFC free insulation, thickness 80 mm (60 mm Mod. ROLL-INDX 1 TN COMPACT / ROLL-INDX 1 BT COMPACT), density 42 kgm³ (back insulation 60mm).
- Automatic defrost and condensate evaporation device without the need for any electricity.
- Large capacity cell makes it possible to insert trolleys up to overall dimensions: 700x900x1860 mm.
- Ergonomic full height handles and magnetic seals on 4 sides.
- Standard lock with key.
- Self-closing doors with 100° opening lock.
- AISI 304 18/10 steel insulated floor for the LT version.
- Bumper on back and door interior in plastic material.
- Refrigerated versions (built-in condensing unit), versions without condensing unit with or without remote unit supplied by us.
- Versions with glass door.

