


Air Curtain Display

TOAM-30-HC~TSL01

 Upright Open Multideck Refrigerator, with Illuminated Sign panel



Dimensions		Build		Technical	
External Width (mm)	762	Exterior Construction	Aluminium or Black powder coated Steel	Temperature Holding	0.5 : 3.3°C
External Depth (mm)	738	Interior Construction	Clear or White coated aluminium, stainless steel base	Refrigerant	R290
External Height (mm)	1994	Air Intake Position	Front	Voltage / Frequency / Phase	220-240V/50Hz/1
Net Volume (Litres)	328	Ventilation Position	Rear	Amps	6.2
Gross Volume (Litres)	723	Clearance Required	102 mm rear, 305 mm above	60Hz model Amps	6.3
Display Area (m ²)	0.67	Cord Length (Meters)	3.04	Wattage	1426
Supplied Shelves	4	Internal Lighting	LED	60Hz model Wattage	1449
Shelf Size (L x D mm)	665 x 430			Defrost Type	Auto
Internal Net Height (mm)	1150				
Unpackaged Weight (kg)	166				
Packaged Weight (kg)	177				
Packaged Dimensions (W x D x H mm)	1071 x 889 x 2128				
Supplied Supports	Leg Levellers (Castors supplied separate)				



Specifications subject to change without notice.
Technical data above related to energy use based on testing of 50Hz or Dual Frequency models
Chart dimensions rounded up to the next whole millimeter (inches rounded up to the 1/8")

UK & Ireland [0800 783 2049](tel:08007832049)
EMEA [+41 61 563 07 05](tel:+41615630705)
Australia [+61 2 9619 9999](tel:+61296199999)


TFIUK@truemfg.com
TrueCHCustomerService@truemfg.com
TrueRefAus@truemfg.com



Air Curtain Display

TOAM-30-HC~TSL01

Upright Open Multideck Refrigerator, with Illuminated Sign panel



Specifications subject to change without notice.
Technical data above related to energy use based on testing of 50Hz or Dual Frequency models
Chart dimensions rounded up to the next whole millimeter (inches rounded up to the 1/8")

UK & Ireland 0800 783 2049
EMEA +41 61 563 07 05
Australia +61 2 9619 9999

TFIUK@truemfg.com
TrueCHCustomerService@truemfg.com
TrueRefAus@truemfg.com

