



Catalogue :

SERIE 900 KORE

Chapter :

CHARCOALS 900 KORE

Article :

B-G9051 | LPG 230V 1N

Code:

19044778

DIMENSIONS AND WEIGHTS

	<u>Net dimensions</u>	<u>Packed</u>
Length	mm 400,00	1.022,00
Depth	mm 930,00	440,00
Height	mm 850,00	1.255,00
Weight	kg 52,00	65,00
Volume	m3 0,32	0,56

ELECTRICITY

230V	50/60Hz	
Power		0,10 kW
Connections	230 V. 1+N+T 2X1,5+T	
	230 V. III+T	
	400 V. III+N+T	

GAS

Power		11,00 kW
Gas type	LPG	
Consumption		0,85 kg/h
Pressure	LPG G30/G31 28-30/37 mbar	

WATER

Not necessary

STEAM

Not necessary

AIR

Not necessary

DESCRIPTION

GAS GRILL TOP, B-G9051 I
 The new Fagor industrial grills do not carbonize food surface and provide a healthy cooking.
 Our grills reach a very high temperature (400°C) that seals the product surface quickly and keeps a more juicy inside .
 Their new features include steam cooking.
 2 mm stainless AISI-304 steel top with rounded edges for easy cleaning. Laser cut and automatic welding for a perfect adjustment of sides between modules with square angle finish.
 Gas heated model with three tubular burners with radiant plates. Control by means of safety valve with thermocouple. Electronic ignition. Stainless steel grill, 340 mm wide. Easy to remove without tools for any easy cleaning.
 Reversible grill to cook different products in a different way:
 _ Grooved side and slanted grill for meat.
 _ Smooth flat horizontal side for fish and vegetables
 Food gets cooked and grilled from direct contact and heat irradiation from underneath burners.
 Grill surface 24 dm²
 Fitted with a cooking fat drainage hole at the front to collect fat and grease from cooking and 12 litre collecting tray at the bottom. Fat collecting trays may be filled with water. Thanks to the heat irradiated by the burners a low intensity steam is produced to cook in a steam atmosphere.
 Removable 130 mm stainless steel anti splash shield, easy to wash. Water-tight and protecting-support controls.
 High temperature protector for the chimney made of enamelled cast iron. Front access to components.
 According to European standards for components and panels temperature, efficiencies and combustion, and sanitary regulations (EN-60335 and EN-203)
 IPX5 grade water protection equipment.
 Maximum power: 11.0 kW - Gas
 It requires an 230V - 1+N power supply.
 Dimensions: 400 x 930 x 850 mm.

SOUND LEVEL

< **65,00 db**

CERTIFICATES

1312CR6178

INSTALLATION - CONNECTIONS

▶ ELECTRICITY	SI	Ø
▶ GAS		R.3/4"G





Catalogue :
SERIE 900 KORE

Chapter :
CHARCOALS 900 KORE

Article :
B-G9051 | LPG 230V 1N

Code :
19044778

SCHEMA - DIMENSIONS

