



**Refrigeration**

Front bar chest coolers

**FRONT BAR CHEST COOLER, BFP-300 I**

**DIMENSIONS**

		<u>Article</u>	<u>Packed</u>
Length	mm	<b>3.000,00</b>	<b>3.040,00</b>
Depth	mm	<b>550,00</b>	<b>590,00</b>
Height	mm	<b>850,00</b>	<b>940,00</b>
Weigth	Kg	<b>135,00</b>	<b>142,00</b>
Volumen	m3	<b>1,40</b>	<b>1,69</b>

**ELECTRICITY**

<u>Electric power</u>	KW	
230V -1+N		<b>0,39</b>
230V - III		<b>2x1,5+T - 4 A</b>
400V - III+N		

**WATER**

Water consumption (lit/h)		<b>0,00</b>
Pressure (Kg/cm2)		

**GAS**

Not used

**STEAM**

Not used

**AIR**

Not used

**REFRIGERATION**

R-134 a

**Certificate EQNET- CE**

SGS-2103-0906-1

**FRONT BAR CHEST COOLER, BFP-300 I**

Stainless steel exterior, .  
 Stainless steel adjustable legs, .  
 Interior bottom in stainless steel .  
 Internal sides of stainless steel.  
 Interior depth with rounded edges and vertical separators.  
 stainless steel grid.  
 Working temperature: +2°C, +6°C at room temperature of 38°C.  
 Removable, ventilated airtight compressor.  
 R-134 A coolant.  
 Right hand unit.  
 Insulation of injected polyurethane. Density 40 kg. No CFC.  
 Evaporator with aluminium fins and copper tube.  
 Static refrigeration.  
 Illuminated general switch. Thermostat temperature control.  
 Operating voltage 220/240 V – I – 50/60 Hz.  
 N. of doors: 6.  
 Capacity (litres): 860.  
 Refrigeration power: 385 W.  
 Dimensions: 3.000 x 550 x 850 mm.

<b>Connections points</b>	<b>X</b>	<b>Y</b>	<b>Z</b>	<b>Diameter</b>	<b>Information</b>
ELECTRICITY	200	5	310		Prever Interruptor diferencial

