

- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- Three levels of shelving plus base
- Self-closing lockable doors with heavy duty magnetic door seals
- Fan forced evaporator cooling
- Internal LED lighting
- HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User friendly Digital controls and internal lighting
- Shelf and shelf support are designed to accommodate 2 x 1/1 GN pan
- Heated door frame for freezer unit
- Heavy duty evaporator and condenser fans
- Heavy duty castors with front wheel brakes












RC1200G2V / XURF1200G2







| Code | Litre | Dimensions (WxDxH mm) | Weight (kg) | Temperature Range | Ambient/ RH% | Voltage | Power (W/A) |
|---------------------------|-------|--------------------------|----------------|----------------------|-----------------|---------|----------------|
| Single glass door fridge | | | | | | | |
| XURC600G1V | 600 | 680x810+30x2000 | 132 | +2 to +8 | 38/40 | 240 | 195/10 |
| Single glass door freezer | | • | • | • | • | | |
| XURF600G1V | 600 | 680x810+30x2000 | 132 | -15 to -18 | 38/40 | 240 | 450/10 |
| Double glass door fridge | | • | • | • | • | | • |
| XURC1200G2V | 1200 | 1340x810+30x2000 | 167 | +2 to +8 | 38/40 | 240 | 400/10 |
| Double glass door freezer | | | | | | | |
| XURF1200G2V | 1200 | 1340x810+30x2000 | 167 | -15 to -18 | 38/40 | 240 | 700/10 |

FED-X UPRIGHT REFRIGERATION ACCESSORIES



| Code | Description | | | | |
|--|--|--|--|--|--|
| Additional Shelf Set | | | | | |
| 12502013416 | Infill shelf for XURC1200G2V, XURC1200S2V, XURF1200G2V and XURF1200S2V | The state of the s | | | |
| 12502012803 | Infill shelf for XURC1410G2V, XURC1410S2V, XURF1410G2V and XURF1410S2V | The state of the s | | | |
| XUR-SHELFSET Optional Stainless Steel | Additional shelf set for upright fridge and freezer units, including one shelving andone pair of runner, suits XURC1200G2V, XURC1200S2V, XURC600G1V, XURC600S1V, XURF1200G2V, XURF1200S2V, XURF600G1V, XURF600S1V, XURC1410G2V, XURC1410S2V, XURC650G1V, XURC650S1V, XURF1410G2V, XURF1410S2V and XURF650S1V | | | | |
| GXE-2-1516 | Runner Set for Upright Refrigeration, XURC1200G2V, XURC1200S2V, XURC600G1V, XURC600S1V, XURF1200G2V, XURF1200S2V, XURF600G1V, XURF600S1V, XURC1410G2V, XURC1410S2V, XURC650G1V, XURC650S1V, XURF1410G2 | | | | |
| Legs | | | | | |
| 12533110010 | Heavy duty Stainless Steel Leg Adjustable Range 140-200mm (per pc) | | | | |