## **FULL GLASS DOOR UPRIGHT FRIDGES & FREEZERS**




- Stainless steel interior and exterior with rounded corners for easy cleaning
- Auto defrost
- Three levels of shelving plus base
- Self-closing lockable doors with heavy duty magnetic door seals
- Fan forced evaporator cooling
- Internal LED lighting
- HFCs and CFCs free foam body insulation
- Tropicalised for Australian conditions
- User friendly Digital controls and internal lighting
- Shelf and shelf support are designed to accommodate 2 x 1/1 GN pan
- Heated door frame for freezer unit
- Heavy duty evaporator and condenser fans
- Heavy duty castors with front wheel brakes











Code	Litre	Dimensions (WxDxH mm)	Weight (kg)	Temperature Range	Ambient/ RH%	Voltage	Power (W/A)
Double glass door fridge							
XURC1410G2V	1410	1480x812+48x2000	208	+2 to +8	38/40	240	415/10
Double glass door freezer							
XURF1410G2V	1410	1480x812+48x2000	208	-15 to -18	38/40	240	865/10

Allow 100mm clearance for installation, all vents must be left clear.

## FED-X UPRIGHT REFRIGERATION ACCESSORIES



Code	Description				
Additional Shelf Set					
12502013416	Infill shelf for XURC1200G2V, XURC1200S2V, XURF1200G2V and XURF1200S2V	The state of the s			
12502012803	Infill shelf for XURC1410G2V, XURC1410S2V, XURF1410G2V and XURF1410S2V	The state of the s			
XUR-SHELFSET  Optional Stainless Steel	Additional shelf set for upright fridge and freezer units, including one shelving andone pair of runner, suits XURC1200G2V, XURC1200S2V, XURC600G1V, XURC600S1V, XURF1200G2V, XURF1200S2V, XURF600G1V, XURF600S1V, XURC1410G2V, XURC1410S2V, XURC650G1V, XURC650S1V, XURF1410G2V, XURF1410S2V and XURF650S1V				
GXE-2-1516	Runner Set for Upright Refrigeration, XURC1200G2V, XURC1200S2V, XURC600G1V, XURC600S1V, XURF1200G2V, XURF1200S2V, XURF600G1V, XURF600S1V, XURC1410G2V, XURC1410S2V, XURC650G1V, XURC650S1V, XURF1410G2				
Legs					
12533110010	Heavy duty Stainless Steel Leg Adjustable Range 140-200mm (per pc)				