


CENTRAL WINE CELLARS

- Side and central walls with double-layered glass and air chamber between them.
- Swing doors that optimize space.
- Ventilated refrigeration system.
- Humidity control to create an optimal wine conservation environment as an option.
- Independent digital thermostat for each environment.
- Tray to collect defrosted water and automatic evaporation. No drain required.
- LED lighting in all perimeters, adjustable by remote control.
- Decorative plinth included as standard. Shelves and hooks should be requested separately.
- Operating temperature: +4°C to +18°C.
- Glasses and door frames heated to avoid condensations



FWC-2301-1CB



FWC-2302-1CB



FWC-2601-1CB



FWC-2602-1CB



FWC-2302-2CB



FWC-2602-2CB

Code	Bottles x Shelves	Dimensions (WxDxH mm)	Weight (kg)	Temperature Range °C	Ambient °C	Voltage	Power (W/A)
Single Zone Temperature							
FWC-2301-1CB	7 x 9	862 x 632 x 2300	277	+4 to +18	40/40	240	1.33/10
FWC-2302-1CB	7 x 18	1697 x 632 x 2300	583	+4 to +18	40/40	240	2.23/15
FWC-2601-1CB	7 x 11	862 x 632 x 2600	294	+4 to +18	40/40	240	1.42/10
FWC-2602-1CB	7 x 22	1697 x 632 x 2600	559	+4 to +18	40/40	240	2.7/15
Dual Zone Temperature							
FWC-2302-2CB	7 x 18	1697 x 632 x 2300	569	+4 to +18	40/40	240	2.52/15
FWC-2602-2CB	7 x 22	1697 x 632 x 2600	593	+4 to +18	40/40	240	2.8/15

Allow 100mm clearance for installation, all vents must be left clear. Prices and specifications are subject to change without notice. Pictures are for illustrative purpose and final product may differ