

WALL-MOUNTED WINE CELLARS

- Side and central walls with double-layered glass and air chamber between them.
- Swing doors that optimize space.
- Ventilated refrigeration system.
- Humidity control to create an optimal wine conservation environment as an option.


- Independent digital thermostat for each environment.
- Tray to collect defrosted water and automatic evaporation. No drain required.
- LED lighting in all perimeters, adjustable by remote control.
- Decorative plinth included as

standard. Shelves and hooks should be requested separately.

- Operating temperature: +4°C to +18°C.
- Glasses and door frames heated to avoid condensations




FWC-2301-1WB



FWC-2302-1WB



FWC-2601-1WB



FWC-2602-1WB



FWC-2302-2WB



FWC-2602-2WB

Code	Bottles x Shelves	Dimensions (WxDxH mm)	Weight (kg)	Temperature Range °C	Ambient °C	Voltage	Power (W/A)
Single Zone Temperature							
FWC-2301-1WB	7 x 9	862 x 632 x 2300	277	+4 to +18	40/40	240	1.28/10
FWC-2302-1WB	7 x 18	1697 x 632 x 2300	583	+4 to +18	40/40	240	2.18/15
FWC-2601-1WB	7 x 11	862 x 632 x 2600	294	+4 to +18	40/40	240	1.36/10
FWC-2602-1WB	7 x 22	1697 x 632 x 2600	559	+4 to +18	40/40	240	2.7/15
Dual Zone Temperature							
FWC-2302-2WB	7 x 18	1697 x 632 x 2300	569	+4 to +18	40/40	240	2.4/15
FWC-2602-2WB	7 x 22	1697 x 632 x 2600	593	+4 to +18	40/40	240	2.68/15

Allow 100mm clearance for installation, all vents must be left clear.

Prices and specifications are subject to change without notice. Pictures are for illustrative purpose and final product may differ