## **PASS-THROUGH DISHWASHER**



- Hood type dishwasher EVO Generation - Concept range
- Hourly production: 60 baskets/ hour - 720 dishes/hour
- Clearance (max ware height):
  440 mm
- Electronic control
- Wash cycles: 90-120-180
- Stainless steel
- · Counterbalanced hood
- Double rotating wash and rinse systems, made of AISI-304 stainless steel
- Wash pump, 600W each
- Drain pump: 70W drainage cycle Safety magnetic switch for hood
- Tank with 4.5 kW heating power

- Tank capacity: 33 litres
- Boiler heating power: 6 kW
- Boiler capacity: 9 litres
- Water consumption: 2.4 litres/ rinse
- Thermostatic temperature control: washing at 60°C and rinsing at 90°C
- Thermostop
- Safety thermostats
- Built-in automatic rinse dispenser and detergent doser
- Built-in non-return valve
- Safety magnetic switch for hood opening

- Adjustable legs
- Supplied with 1 base basket;
  1 plate basket and 2 cutlery containers
- Watermark approved
- Can be converted to single phase
- Precision of working temperatures
- Temperature control by electronic probes.
- Accuracy±2°C
- Configurable control
- i-ERROR DIAGNOSIS
- SAT menu Error identification on screen
- Indications on the screen



| Code      | Dimensions<br>(WxDxH mm) | Weight<br>(kg) | Voltage/Hz           | Power<br>(kW/A)        |
|-----------|--------------------------|----------------|----------------------|------------------------|
| CO-142BDD | 630x750x1465             | 92             | 415/50<br>Multipower | 11.1/3~N<br>Multipower |