



Catalogue:

COUNTERS NEO

Chapter:

GLOBE ADVANCE COUNTERS

Article :

EAMCP-225 230V 1N 50Hz

| | , | " | u١ | _ | • | | |
|---|---|---|----|---|---|---|---|
| 1 | 9 | 0 | 3 | 7 | 8 | 0 | 5 |

| DIMENSIONS AND | WEIGHTS | Net dimensions | <u>Packed</u> | | |
|-------------------------|---|----------------|-------------------|--|--|
| Length | mm | 2.250,00 | 825,00 | | |
| Depth | mm | 768,00 | 2.353,00 | | |
| Height | mm | 850,00 | 1.060,00 | | |
| Weight | kg | 169,00 | 174,00 | | |
| Volume | m3 | 1,47 | 2,06 | | |
| E. E. G. T. D. G. T. J. | | | | | |
| ELECTRICITY | 230V | 50Hz | 0.00 141/ | | |
| | Power | | 0,20 kW | | |
| Connections | 230 V. 1+N+T | | | | |
| | 230 V. III+T | | | | |
| | 400 V. III+N+T | | | | |
| <u>GAS</u> | Not necessary | | | | |
| | ,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,, | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| WATER | Not necessary | | | | |
| | | | | | |
| | | | | | |
| STEAM | Not necessary | | | | |
| | | | | | |
| | | | | | |
| AIR | Not necessary | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | R-600a | | |
| | Refrigeration po | ower | 0,36 | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | | | | | |
| | Internal gross of | apacity litres | 546 | | |
| | Climat class | 4 | | | |
| SOUND LEVEL | | | < 65,00 db | | |
| | | | | | |
| | | | | | |
| INSTALLATION - | CONNECTION | <u>s</u> | Ø | | |
| | _ | | | | |

DESCRIPTION

REFRIGERATED CENTRAL COUNTER ADVANCE, EAMCP-225

SPECIFICATIONS

High quality austenitic stainless steel inside and outside (except for galvanized back panel).

40 kg/m3 injected polyurethane isolation. 60 mm thick side walls, while the ceiling is 40 mm thick with a 50 mm worktop on it to make a total 90 mm thickness.

Copper piping and aluminium flaps evaporator.

HACCP system that keeps running logs.

Digital display for electronic and digital control of temperature and defrosting.

The controls are integrated in the front panel for a better protection against dirt. IPX5 compliant, the controls are protected against water splash and jets.

Acoustic and visual alarm connected to three sensors at strategic spots. They provide a total control and block the compressor in case of dirt or failure.

Opened door delay alarm.

Easier loading and unloading thanks to its door self-closing and stay

Removable and height adjustable plastic covered steel shelves for easy cleaning (GN1/1 size).

Equipment per door: 1 GN 1/1 grid and 2 sets of height adjustable tray slides

Built in drainage to get rid of waste liquids inside the unit.

Embedded bottom and curved panels inside for easy cleaning and maintenance.

Height adjustable stainless steel legs. Working temperature: from -2 °C up to +8 °C.

Climatic class 4.

Doors: 4+4

Gross capacity: 546 L Cooling power: 360 W Electric power: 200 W

Coolant: R-600a

Dimensions: 2250x768x850 mm













Catalogue :

COUNTERS NEO

Chapter:

GLOBE ADVANCE COUNTERS

Article:

EAMCP-225 230V 1N 50Hz

Code:







