



## ECOMAX 702 UTENSIL WASHER

### Utensil Washer ecomax 702

Cycle times*	120/360 sec
Capacity per hour*	up to 30 cycles
Wash/rinse temperature	60 - 65°C / min 82°C
Tank capacity	80 l
Fresh water consumption/cycle	4.5 l
Wash pump	2.9 kw
Heating booster/tank	9 kw / 3.3 kw
Total loading	12 kw
Rated voltage	400V/50Hz/3/N
Width/Depth/Height	780/945/1765 mm
Loading height	630 mm
Rack size	600 x 760 mm

\*hot water connection

### FEATURES

- Rotating top and bottom wash system to distribute the wash water evenly over the dishes
- Deep-drawn wash tank bottom, no hygiene problems with corners and edges
- Thermostop-function for guaranteed rinse temperatures
- Removal of wash and rinse arms without any tools
- Easy access to all parts
- Flat surface of control panel
- Loading of high trays and pots: up to 630 mm loading height
- 150 mm floor clearance
- Electronic control
- Made completely out of stainless steel
- Tank covered with strainer made of stainless steel
- Back flow prevention & Watermark Approved

### STANDARD EQUIPMENT

- Stainless steel base rack, 8 tray support insert & universal 500x500mm rack - B-00-07
- Fully equipped with detergent & rinse aid dispenser, rinse pressure pump and drain pump
- Electric plug & lead, water supply hose & drain hose

### Utensil Washer ecomax 702

Order-No.	Description	
Ecomax702	with rinse pressure & drain pumps, detergent & rinse aid dispensers, S/S base rack, 8 tray support insert (323637) and universal rack B-00-07	
323753	Insert 568 x 665 mm suitable for plates, bowls, sheets, etc.	

Connection to cold water or reduced voltage can extend the heating time and the program runtime.

For machine protection the water hardness should not exceed 3°dH, if higher we recommend using a water softener or an external water treatment system.