



## Dishwashing

### Conveyor dishwashers

## CONVEYOR DISHWASHER, FI-460 R

### DIMENSIONS

		Article	Packed
Length	mm	2.650,00	2.750,00
Depth	mm	780,00	960,00
Height	mm	1.580,00	1.900,00
Weigth	Kg	434,00	628,00
Volumen	m3	3,27	5,02

### ELECTRICITY

Electric power	KW	
230V - I+N		
230V - III		3x70+T - 180 A
400V - III+N		4x35+T - 125 A

### WATER

Water consumption (lit/h)	450,00
Pressure (Kg/cm2)	2 - 4

### GAS

Not used

### STEAM

Not used

### AIR

Not used

### LEVEL SOUND

(dB) 72

### CONVEYOR DISHWASHER, FI-460 R

Made of stainless steel.

Two conveyor speeds:

1st. Speed: 170 baskets/h. 2nd. Speed: 255 baskets/h.

Splash-guard module at entry.

Two wash modules and double rinse module.

Dividing curtains highly resistant to chemical agents and heat.

Wash tanks 90 litres each. Tray-filters removable for cleaning.

Wash pumps 2.2 kW. Tank heated by means of shielded elements, 12 kW. Thermostatically adjusted. (wash temperature: 60 °C).

Pre-rinse tank heated by means of shielded elements, 5 kW. Rinse pump 0.26 kW.

Built-in rinse water boiler (34.5 kW). Safety thermostat.

Analogic thermometers for wash and rinse water temperature.

Water consumption: 450 l/h.

Magnetic switches for wash, rinse and door opening.

Energy economiser system.

Motor-reducer: 250 W.

Baskets equipment: 2 x CT-10, 2 x CP-16/18, 1 x CV-16/105, and 16 cutlery containers.

Power: 55.9 kW.

Dimensions: 2.650 x 780 x 1.580 mm.

Connections points	X	Y	Z	Diameter	Information
ELECTRICITY	1.250	50	1.440		Prever Interruptor diferencial
DRAIN	1.750	425	130	38	
SOFT HOT WATER	1.230	630	240	3/4"	Prever llave de corte en la toma
DRAIN	850	425	130	38	

