



Catalogue:

OTHER REFRIGERATION

Chapter:

**DISPLAY TRAYS** 

Article ·

VTP-175 RC Remote Curve Gris 230V 1N 50H

Code: 19005522

DIMENSIONS AND WEIGHTS		Net dimensions	Packed
Length	mm	1.732,00	480,00
Depth	mm	415,00	2.353,00
Height	mm	278,00	530,00
Weight	kg	59,00	62,00
Volume	m3	0,20	0,60
ELECTRICITY	230V	50Hz	
	Power		<b>0,19</b> kW
Connections	230 V. 1+N+T	2X1,5+T - 2 A	
	230 V. III+T		
	400 V. III+N+T		
GAS	Not necessary		
WATER	Not necessary		

**STEAM** Not necessary

<u>AIR</u> Not necessary

R-134a

SI

Refrigeration power 0,178

Climat class

SOUND LEVEL < 65,00 db

**CERTIFICATES** SGS-2103-0906-1

INSTALLATION - CONNECTIONS Ø

► ELECTRICITY

DESCRIPTION

OVER COUNTER DISPLAY CASES, VTP-175 RC

**SPECIFICATIONS** 

High quality austenitic stainless steel inner tray.

Anodized aluminium outside panels. Glass with PVC on the sides. Curved glass cover (one piece) or flat cover (two pieces) and glass slidina doors.

40 kg/m3 injected polyurethane isolation. CFC free.

It can fit GN -1/3, 40 mm deep containers. The containers are included in the standard equipment.

The cooling unit may be inside or outside the room and can be placed at a distance from the cabinet.

Remote cooling unit versions include the cooling unit as part of the standard equipment. Its dimensions are 310 x 360 x 240 mm and the

maximum distance to the cabinet is 1.5 m. Cold plate with copper tube evaporator. Emergency waste water drainage.
Electronic thermostat for temperature control.

Shielded inner lighting system.

Lighted power switch.

Working temperature: +4 °C, +8 °C (Room temperature: 32 °C).

Glass type: Bended Containers capacity: 9\*GN1/3 Cooling unit type: Remote Electricity consumption: 184 W

Coolant: R-134a

Dimensions: 1.732x415x278 mm















Catalogue :

OTHER REFRIGERATION

Chapter:

**DISPLAY TRAYS** 

Article:

VTP-175 RC Remote Curve Gris 230V 1N 50H

Code : 19005522

## SCHEMA - DIMENSIONS









