



Catalogue : OTHER REFRIGERATION

Chapter : DISPLAY TRAYS

Article :

VTP-175 RP Remote Flat Gris 230V 1N 50Hz

Code: 19005526

DESCRIPTION

| DIMENSIONS AND WEIGHTS Length mm Depth mm Height mm Weight kg Volume m3 ELECTRICITY 230V Connections 230 V. 1+N+T 230 V. 11+N+T 230 V. 11+N+T 230 V. 11+N+T 230 V. 11+N+T GAS Not necessary WATER Not necessary STEAM Not necessary AIR Not necessary | Net dimensions 1.732,00 415,00 278,00 59,00 0,20 50Hz 2X1,54 | Packed 480,00 2.353,00 62,00 0,60 0,19 kW |
|---|---|--|
| DepthmmHeightmmWeightkgVolumem3ELECTRICITY230VConnections230 V. 1+N+T230 V. 11I+T230 V. 11I+TGASNot necessaryWATERNot necessarySTEAMNot necessary | 415,00 278,00 59,00 0,20 50Hz | 2.353,00 530,00 62,00 0,60 0,19 kW |
| HeightmmWeightkgVolumem3ELECTRICITY230VConnections230 V. 1+N+T230 V. 11+T230 V. 11+TGASNot necessaryWATERNot necessarySTEAMNot necessary | 278,00 59,00 0,20 50Hz | 530,00 62,00 0,60 0,19 kW |
| Weight Volumekg m3ELECTRICITY Connections230V PowerConnections230 V. 1+N+T 230 V. 11+T 400 V. 11+N+TGASNot necessaryWATERNot necessarySTEAMNot necessaryAIRNot necessary | 59,00 0,20 50Hz | 62,00 0,60 0,19 kW |
| Volumem3ELECTRICITY230V PowerConnections230 V. 1+N+T 230 V. 1I+T 400 V. III+N+TGASNot necessaryWATERNot necessarySTEAMNot necessaryAIRNot necessary | 0,20 50Hz | 0,60 0,19 kW |
| ELECTRICITY230V PowerConnections230 V. 1+N+T 230 V. 11+T 400 V. 11+N+TGASNot necessaryWATERNot necessarySTEAMNot necessaryAIRNot necessary | 50Hz | 0,19 kW |
| PowerConnections230 V. 1+N+T 230 V. 1II+T 400 V. 1II+N+TGASNot necessaryWATERNot necessarySTEAMNot necessaryAIRNot necessary | | |
| Connections230 V. 1+N+T 230 V. 1II+T 400 V. III+N+TGASNot necessaryWATERNot necessarySTEAMNot necessaryAIRNot necessary | 2X1,54 | |
| 230 V. III+T 400 V. III+N+T SGAS Not necessary WATER Not necessary STEAM Not necessary AIR Not necessary | 2X1,54 | +T - 2 Α |
| A00 V. III+N+T GAS Not necessary WATER Not necessary STEAM Not necessary AIR Not necessary | | |
| GASNot necessaryWATERNot necessarySTEAMNot necessaryAIRNot necessary | | |
| WATERNot necessarySTEAMNot necessaryAIRNot necessary | | |
| STEAM Not necessary AIR Not necessary | | |
| STEAM Not necessary AIR Not necessary | | |
| <u>AIR</u> Not necessary | | |
| | | |
| Refrigeration po | | |
| | wer | R-134a 0,178 |
| Climat class | 4 | |
| SOUND LEVEL | | < 65,00 db |
| CERTIFICATES | SGS-2103-0906-1 | |
| INSTALLATION - CONNECTIONS | <u>.</u> | Ø |
| ► ELECTRICITY | | SI |

| OVER COUNTER DISPLAY CASES, VTP-175 RP |
|---|
| SPECIFICATIONS |
| High quality austenitic stainless steel inner tray. Anodized aluminium outside panels. Glass with PVC on the sides. Curved glass cover (one piece) or flat cover (two pieces) and glass sliding doors. 40 kg/m3 injected polyurethane isolation. CFC free. It can fit GN -1/3, 40 mm deep containers. The containers are included in the standard equipment. The cooling unit may be inside or outside the room and can be placed at a distance from the cabinet. Remote cooling unit versions include the cooling unit as part of the standard equipment. Its dimensions are 310 x 360 x 240 mm and the maximum distance to the cabinet is 1.5 m. Cold plate with copper tube evaporator. Emergency waste water drainage. Electronic thermostat for temperature control. Shielded inner lighting system. Lighted power switch. |
| Working temperature: +4 °C, +8 °C (Room temperature: 32 °C). Glass type: Flat |
| Containers capacity: 9*GN1/3 |
| Cooling unit type: Remote |
| Electricity consumption: 184 W |
| |

Coolant: R-134a Dimensions: 1.732x415x278 mm

000





Catalogue : OTHER REFRIGERATION

Chapter : DISPLAY TRAYS

Article : VTP-175 RP Remote Flat Gris 230V 1N 50Hz

Code : 19005526

SCHEMA - DIMENSIONS

